



INDUSTRIAL Fuel Air Separation System

INSTALLATION MANUAL DETROIT SERIES 60[®] ENGINES 12.7L Model Years 1987-2002



**PLEASE READ
THESE INSTRUCTIONS
THOROUGHLY
BEFORE BEGINNING
INSTALLATION**

Part No. A3SPBT405

NOW WITH DEMAND FLOW

Revised 10/14/2022



Proudly Made in the USA

**www.airdogdiesel.com
1-573-635-0555 or
1-877-463-4373**

Providing "Test Cell Performance" in "Real World Conditions" Since 1993

PATENT

www.AirDogDiesel.com/patents

AirDog[®] INDUSTRIAL Fuel Air Separation System

THE RIGHT CHOICE FOR YOUR DIESEL ENGINE

4G-HD Fuel Pump

Pump shaft, stabilized with bearings on each end, holds the gerotor in virtually perfect alignment for quiet running and extended longevity!



Low Fuel Pressure Switch and LED Indicator

Lets you know when to service the fuel filter and water separator before suffering power loss.
NO MORE GUESSING!



Bearings



LoveJoy Coupler System

The LoveJoy Coupler System is self-aligning and eliminates virtually all vibrations.



Positive Air Separation
with primary air discharge port.



Dual Port Pump

Balances the gerotor for quiet operation and higher flows.



Demand Flow System

Easy installation, only one small line connected to the engine return line to return air/vapor to the tank.



Protective Wire Screen

In water separator nipple.



Adjustable Regulator

For just the right fuel pressure.

6 Micron Particulate Filters
Long-Lasting MicroGlass Media

Water Separator/Prefilter
Long-Lasting Wire Mesh Media

CARB Executive Orders D-595-5 & D-595U-6 permit the advertisement, sales and installation of PureFlow Technologies AirDog[®] Diesel Fuel Systems in California on 2020 and older model year on-road diesel vehicles and off-road diesel vehicles/equipment.

SYSTEM OVERVIEW

Welcome to the **AirDog® Heavy Duty Industrial**
Fuel Air Separation System for Class 8 Trucks

The **AirDog®**, with **ADVANCED FUEL AIR SEPARATION, DEMAND FLOW, ADJUSTABLE REGULATOR, LOW PRESSURE SENSOR with LED INDICATOR** and the **4G-HD FUEL PUMP**, is a premium fuel filtration and delivery system for the **Detroit Diesel Series 60®** engine, model years 1987 thru 2002.

Specifically, if the fuel pressure/flow to the injector, even with entrained air and vapor removed, is insufficient to totally fill the injector barrel on the up stroke of the plunger, a void or low pressure will form that allows vapor to re-form within the injector. The result, “injector lag”, is just another name for “delayed injection timing”. No matter what term is used, it leaves the engine with increased fuel consumption, lost power, and increased exhaust emissions.

The Detroit Diesel Series 60® engine, model years 1987 thru 2002, utilizes “FOR-SEAL” fittings with steel lines on the high pressure side of the transfer pump. These fittings have small passageways and are restrictive to the fuel flow to the engine. To maximize the efficiency of the 1987 thru 2002 engines, it is necessary to replace the restrictive fuel fittings and lines with the larger and less restrictive lines & fittings.

The **“Upgrade” kit is NOT included** with the Detroit installation kit, although the complete and detailed instructions are included!

Contact PureFlow® Technologies at 1.573.635.0555 for additional information and ordering!

All AirDog® products are manufactured with a personal touch,
unsurpassed attention to detail and the most stringent quality assurance!

TYPICAL INSTALLATION LAYOUT



The **AirDog®** requires only one small return line connected to the engine return line, for quick and easy installations.

TABLE OF CONTENTS

Section 1.....	Table of Contents
Section 2.....	Installation and Safety Guidelines
Section 3.....	Parts List

Installation Procedures

Section 4.....	Selecting the Best Mounting Location
Section 5.....	Mounting the AirDog® & Mounting Brackets

Fuel Lines, Fittings & Low Fuel Pressure Sensor Switch

Section 6A.....	Fittings & Pressure Sensor
Section 6B.....	Fuel Line from AirDog® to Engine
Section 6C.....	AirDog® Fuel Return to Tank
Section 6D.....	From Tank to AirDog®

OPTIONAL Fuel System Upgrade (Sold as Separate Kit, Not Included)

Section 7A.....	Engines Without a Secondary Fuel Filter
Section 7B.....	Engines With a Secondary Fuel Filter

Wire Harness

Section 8.....	Wire Harness
Section 9.....	Initial Start Up

Maintenance

Section 10.....	Filter Service
-----------------	----------------

Section 2

Installation & Safety Guidelines

The installation of your AirDog® can be made relatively easy by following the steps outlined in this manual, and:

1. Inventory the package components. Immediately notify PureFlow® Technologies, Inc., of any missing or damaged parts.
2. Read the installation manual completely. Understand how the system operates and the installation recommendations before beginning.
3. Proper location of the AirDog® on the vehicle is essential. Consider hazards presented to the equipment by road debris and the elements.
4. The installation recommendations and guidelines contained herein are suggestions only. Individual installations may vary.
5. Use diesel compatible thread sealer when installing fittings with NPT threads. (Loctite® 545 Thread Sealer is diesel compatible.)

DO NOT REMOVE FACTORY INSTALLED SECONDARY FUEL FILTERS. REMOVAL OF A FACTORY INSTALLED SECONDARY FUEL FILTER MAY VOID YOUR ENGINE WARRANTY.

SAFETY GUIDELINES

CAUTION: Chock the vehicle's tires to prevent rolling.

CAUTION: Disconnect the battery cables before proceeding with the AirDog® installation.

CAUTION: Wear safety glasses when operating power tools such as drills and grinders or when using a punch or chisel.

CAUTION: Do Not drill into or weld the top of the frame rail or within 1-½" of the frame rail flange on the side of the frame rail.

CAUTION: Route the fuel lines and electrical harnesses keeping them away from hot exhaust components and/or moving parts. Properly secure the fuel lines and electrical harnesses to prevent chafing using zip ties included in installation kit.

CAUTION: Do not subject the AirDog® system directly to high-pressure wash systems. Doing so may damage seals and electrical components, and such damage is NOT covered under warranty.

**If you are uncertain of any installation procedure, please call:
PureFlow® Technologies, Inc. at 573-635-0555 for technical assistance.**

NOTE: The pictures used in this manual are for example only and may not depict the exact components as found on your truck.

PureFlow® Technologies, Inc.





AirDog® FPII-150

Detroit Series 60 1987-02



Section 3

Installation Parts List



Parts List

QTY	Description	Part Number	Image
1	Installation Manual	206-1-0405	
1	AirDog® - with Serial Number Plate Fuel Filter FF200-MG-6 201-3-0020 Water Separator WS200-WS	FPII-150	
1	Wire Harness w/ Indicator Light & Dash Plate Includes: 1 ea Indicator Light (5G-1-1-47674) 1 ea Dash Plate (201-3-0004-S-M716)	5E-2-010 908-5G-1-1-47674	
1	3/8" Low Pressure Hose (Air/Vapor Return Line) - 7 ft Section	4C-1-02-05-010-7FT	







ADFK-405 Installation Kit

1	Fuel Pressure Sensor	908-5C-9-007 <i>or</i> 908-5C-9-0010	
15	12" Zip Ties	5H-2-1-12	







908-00-0304 Frame Mount Bracket Kit

1	Left Mounting Bracket	002-3C-0003	
1	Right Mounting Bracket	002-3C-0004	
1	901-08-0100 Frame Mount Bracket Bolt Kit Includes: 4 ea 3/8-16 x 1-1/4 HHCS 4 ea 1/4-20 x 2 SHCS 908-08-0100-N Nut Packet 4 ea 3/8-16 Hex Nut & 4 ea 1/4-20 Hex Nut 908-08-0100-W Washer Packet 4 ea 3/8 Split Lock Washer & 4 ea 1/4 Split Lock Washer	1J-1-C20SZ 1L-A32C <i>1S-1-CSZ & 1S-1-AC</i> <i>1R-6-CSZ & 1R-6-AC</i>	



908-08-0800-UNIV AirDog® FPII Basic Fitting Kit - Universal Applications

2	#10M JIC x 1/2 M NPTF Straight Connector	4A-1-01-10-08-S	
2	#10M JIC x #10F JICX 90° Swivel Nut Elbow	4A-2-04-10-10-S	
2	#8M JIC x 1/2 M NPTF Straight Connector	4A-1-01-08-08-S	
2	#8M JIC x #8F JICX 90° Swivel Nut Elbow	4A-2-04-08-08-S	
1	#6M JIC x 1/4 M NPTF Straight Connector	4A-1-01-A-C-SZ	
1	3/8 ID, 7/8 OD Rubber Grommet	5J-1-1-04-2758	

908-01-0405-RLFK Return Line Fitting Kit

1	#6M JIC x 1/4 M NPTF Straight Connector	4A-1-01-A-C-SZ	
1	#8M JIC x #8F JICX x 1/4 NPTF Port GagePort	4A-1-11-08-08-4P	
2	#6F JICX x 3/8 Push-lock Hose Barb	4A-1-09-06-06-B	
1	#6M JIC x #6F JICX 90° Street Elbow	4A-2-04-06-06-S	
1	3/8-18 M NPTF x 3/8-18 F NPTF x 3/8-18 F NPTF Tee	4A-4-01-06-S	
1	#6M JIC x 3/8 M NPTF Straight Connector	4A-1-02-06-06-S	

SBK-1000 Sandwich Bracket Kit

OPTIONAL	1	Sandwich Mounting Bracket Kit for AirDog® & Champ Includes: 1 Front Bracket (002-3C-0010-SBF), 1 Back Bracket (002-3C-0011-SBB), & 1 Universal Bracket (002-3C-0006PCB)	908-00-8888	
	1	901-08-0100-SB Hardware Kit Includes: 4 ea 3/8-16 x 1 FHSCS 3 ea 3/8-16 x 3-1/2 HHCS 3 each 3/8-16 x 4-1/2 HHCS 7 ea 3/8-16 Hex Nut 7 ea 3/8 Split Lock Washer	1M-C16SZ 1J-1-C56SZ 1J-1-C72SZ 1S-1-CSZ 1R-6-CSZ	

Selecting the Best Location to Mount the AirDog®

Installing the AirDog® at the proper location on the vehicle is most important. When deciding where to locate the AirDog®, the following points should be considered:

- Best relationship to the transfer pump and the original primary fuel filter location
- Protection from the elements and road debris
- Accessibility for service

CAUTION: DO NOT mount the AirDog® directly on the engine. Mounting the AirDog® directly on the engine will immediately VOID your AirDog® Warranty!

Pictures below show examples of different AirDog® installations. There are many variations in the arrangements of the components on the various trucks. With a little ingenuity, the AirDog® can be successfully installed on any Class 8 Truck.



This installation shows the AirDog® mounted under the steering column ahead of the shock absorber. Plenty of room here!

NOTE: Check for clearance with the tire turned both toward and away from the AirDog®!

Selecting the Best Mounting Location, cont'd



This picture finds space to mount the AirDog® on a bracket in the location of the original primary fuel filter!



This installation on a short nose “Day Cab” is on the driver’s side, behind the battery box.



This picture shows how to find space to mount the AirDog® to the rear of the shock absorber.

OPTIONAL KIT AVAILABLE (PN: SBK-1000)

NO DRILL Universal Sandwich Mounting Bracket

Determine which holes in bracket 1 that you are going to need by holding it up to the frame of your vehicle.



Use mounting hardware to mount bracket 1 to bracket 2. The position of bracket 2 can be adjusted vertically and horizontally to suit your particular needs.

Using product mounting hardware, mount product to brackets.

Install 2 of the frame bracket bolts in top of bracket 1 & bracket 3. Slide over frame and install bottom bolt.

Note: 3.5" and 4.5" bolts are included. Use the length best suited to your vehicle's frame width.

Tighten bolts as needed.
Install filter or filter and water separator as applicable.



Section 5

Mounting the AirDog®

Mounting the AirDog® on the Truck's Frame (Drilling Method)

- 5-1. Disconnect the fuel lines and remove the primary fuel filter.



- 5-2. Mount the AirDog® as close to the location of the primary fuel filter as possible. This will allow you, in most cases, to use the original fuel supply line from the fuel tank and also the fuel line to the engine.

- 5-3. Loosely assemble the mounting brackets and filters to the AirDog®.

- 5-4. Hold the AirDog®, with the brackets and filters attached, next to the frame at the selected mounting location. Check for clearance.



NOTE: If mounted between the frame and steer tire, turn the steering wheel fully to the left and right to check for tire clearance.

Intalling the AirDog® on the Truck's Frame, cont'd

5-5. Hold the AirDog® at the selected mounting location on the frame. Mark and center punch each hole location.



5-6. Drill a 3/8" hole at each of the 4 previously marked locations.

WARNING! DO NOT DRILL INTO OR DAMAGE ANY Wire, AIR LINES OR OTHER COMPONENTS LOCATED BEHIND THE FRAME RAIL.

5-7. Loosely assemble the mounting brackets to the frame.

5-8. Mount and loosely assemble the AirDog® on the brackets.



5-9. After mounting the AirDog® on the brackets, snug the fasteners to achieve a good relaxed fit.

5-10. Properly tighten all of the fasteners.

NOTE: These steps are necessary to prevent stress cracks from forming in the mounting brackets due to vibration.



FUEL LINE OVERVIEW

The AirDog® has been engineered to eliminate fuel related problems. It is important that the fuel lines are assembled and installed properly so as not to cause fuel flow restriction.

When possible, use the fuel lines that are on the vehicle. This will reduce your installation costs and make the installation go much more quickly.

NOTE: On various class 8 trucks, the manufacturer may use “plastic” or other than traditional steel braid fuel lines. These lines require special fittings. The fittings used with the original primary fuel filter are specific to the fuel lines used on the truck. When possible, mount the AirDog® in the location that will allow the use of the original fuel lines and fittings.


Inspect the original fuel lines for size, length, and condition. If the fuel lines are in good condition and the correct size and length to adequately reach the AirDog®, you may want to go ahead and use them. If any of the fuel lines need to be replaced, it is recommended that the fuel lines selected meet or exceed SAE 100R5 requirements.

Fuel Supply Line: The fuel supply lines from the tank to the AirDog® and to the engine should be size 10, or at the absolute minimum, size 8.

Air/Vapor Return Line: The AirDog® return line should be connected to the engine’s return line, low pressure side. A size 6 line for the Air/Vapor return line is adequate.

Primary Fuel Filters: It is most important that there are no fuel filters between the fuel tank and the AirDog® or between the AirDog® and the engine’s transfer pump to plug and cause fuel flow issues. These filters must be removed from the system as part of the AirDog® installation.

Secondary Fuel Filters: DO NOT REMOVE SECONDARY FUEL FILTERS. This is the filter between the transfer pump and the engine head.



Section 6

Fuel Lines, Fittings & Pressure Sensor

Installing the Fuel Fittings and Pressure Sensor

IMPORTANT: Use diesel compatible thread sealer when installing NPT fittings.

NOTE: Below pictures illustrate the installation of straight fittings - #8 JIC and #10 JIC fittings have been included - you will use one or the other based on your fuel line size. In some instances 90° fittings may be required to connect the fuel lines to the AirDog®. Therefore, two 90° fittings have been included in the kit.

6A-1. Install a straight #10 (or #8) JIC x ½" NPT fuel fitting in the AirDog® fuel port marked "ENGINE".



6A-2. Install a straight #10 (or #8) JIC x ½" NPT fuel fitting into the fuel inlet port next to the regulator marked "FUEL IN".

6A-3. Install the ¼" NPT x #6 JIC Air/Vapor return fitting into the Air/Vapor return port marked "TANK".



6A-4. Remove the 1/8" NPT plug in the 45° elbow. Install the pressure sensor into the elbow.

**Section 6B: Connecting the AirDog® Pressure Line
to the Transfer Pump on the Engine**

6B-1. Connect the original fuel line from the primary fuel filter to the transfer pump (Step 5-1) to the AirDog® out to "ENGINE" port. If the fuel line is not in good condition or the proper length to make the connection, replace it with a new fuel line.



Note: This engine does not have a secondary fuel filter.



Connecting the AirDog® Fuel Line to the Transfer Pump on the Engine, cont'd

6B-2. When replacing the fuel line connecting the AirDog® to the engine transfer pump, measure and cut the length of fuel line required, when properly routed, to make the connection. Assemble the fuel line per standard procedures.

6B-3. Connect one end of the fuel line to the AirDog® port marked “ENGINE”.



Install a 90° fitting
as needed



Detroit Diesel Series 60®
fuel transfer pump fuel Inlet

6B-4. Route the new fuel line from the AirDog® to the transfer pump. Connect the fuel line to the transfer pump fuel inlet fitting. Properly tighten the fittings. Secure the fuel line with zip ties as necessary to prevent abrasion and chaffing.

SECTION 6C: Installing the AirDog® Return Line

The AirDog® returns entrained air & vapor to the fuel tank. It is best to connect the AirDog® Air/Vapor return line directly to the engine fuel return line. Be sure to connect it after the pressure regulator.


NOTE: it is recommended to use a # 6 size line for the Air/Vapor return.

Connecting the AirDog® Air/Vapor return to the engine fuel return line

6C-1. Disconnect the fuel return line connected to the Rail Pressure Regulator at the back of the head.



Engine Fuel
Return Line



6C-2. Insert a Tee between the engine rail pressure regulator and the return line to connect the AirDog® Air/Vapor return line.

NOTE: Some class 8 trucks may have a cab with a short hood. This style of truck will have the engine recessed into the firewall making the return fuel fitting on the back of the head difficult to reach. If the truck you are installing the AirDog® on has this style cab, **it may be easiest to connect the AirDog® Air/Vapor return line directly to splitter Tee .**

Installing the AirDog® Return Line, cont'd

For trucks with only one fuel tank, it may be easiest to connect the AirDog® return line directly to the fuel tank. Keep in mind that the #6 return line included with the AirDog® is only long enough to connect to the engine return line at the engine.

6C-3. If the fuel tank has an extra port, as shown in photo, remove the plug.



6C-4. Install a 3/8" NPT x #6 JIC fitting into the port. Use a bushing (not included), if necessary.



6C-5. To install the Air/Vapor return line in a tank with no extra port, install a 3/8" Tee fitting in the engine return line at the fuel tank.




6C-6. The filter assembly has return fuel from the engine running through it to heat the incoming fuel. When removing this filter, re-connect the return line, from the engine to the return line to the tank with the 3/8" Tee. Connect the AirDog® return line at the Tee.

6C-7. Measure and cut a length of fuel line required, when properly routed, to connect from the AirDog® Air/Vapor return fitting to the fuel return Tee.



AirDog®
Air/Vapor Return Port



6C-8. Assemble the fuel line using standard procedures for push lock fittings (see page 12).

6C-9. Route and connect the Air/Vapor return line to the air/vapor return fitting on the AirDog® and the return Tee. Properly tighten the fittings. Secure the fuel line with zip ties as necessary to prevent abrasion and chafing.

Section 6

Fuel Lines

Connecting the AirDog® fuel supply line to the Fuel Tank

6D-1. Inspect the fuel supply lines that connect the fuel tank(s) to the primary fuel filter for size, length, and condition. If a fuel line has deteriorated or if it is too short to connect to the AirDog®, replace it or make an extension as necessary.

6D-2. If it is necessary to replace the fuel line, measure and cut the length of fuel line required when properly routed and secured, to make the connection. Assemble the fuel line per standard procedures.

6D-3. Route the fuel supply line from the fuel tank to the fitting on the AirDog® fuel inlet port marked “FUEL IN”.



6D-4. Connect the fuel supply line from the fuel tank to the fitting. Secure the line with zip ties to prevent chafing and abrasion.

Section 7: OPTIONAL AirDog® Detroit Series 60 Fuel Line Upgrade
OR continue on to page 24 for start-up procedure...

Optional Kit available from PureFlow Technologies, Inc. - this kit is NOT included but recommended for optimal fuel system performance.

Section 4: AirDog® Detroit Series 60 Fuel Line Upgrade Overview

The Detroit Series 60 engine utilizes “FOR-SEAL” fittings with steel lines on the high pressure side of the transfer pump. These fittings have small passageways and are restrictive to the fuel flow to the engine. To maximize the efficiency of the Series 60 engines, it is necessary to replace the restrictive fuel fittings and lines with the larger and less restrictive lines and fittings. These fittings are supplied with the AirDog® installation kit.

AirDog®
 #8 JIC x 14mm
 Passageway **0.375” ID**



14mm “FOR-SEAL”
 Fitting **0.240” ID**
 Passageway

NOTE: Secondary fuel filters are optional on Detroit Diesel Series 60 engines. Section **7A** is for engines **WITHOUT** secondary fuel filters. Section **7B** is for engines **WITH** secondary fuel filters.



Detroit Series 60 WITHOUT
 Secondary Fuel Filter. Steel line carries
 fuel from transfer pump directly to the engine head.



Detroit Series 60 WITH
 Secondary Fuel Filter

Section 7


Fuel Line Upgrade

Section 7A: Series 60 Engines **WITHOUT** a Secondary Fuel Filter

7A-1. Disconnect the steel fuel line from the “FOR-SEAL” fuel fitting at the fuel “OUT” port on the transfer pump and remove OE Fuel fitting.



7A-2. Install the new “Ported” 16mm x #8 JIC fitting in the transfer pump fuel “Out” port **OR** the “Ported” 1/4” M NPT x #8 M JIC fitting.



7A-3. Disconnect the OE fuel supply line from the “FOR-SEAL” fuel fitting at the back of the head and remove the fitting.

NOTE: You may remove the OE steel fuel line from the engine.

7A-4. Install the extended 3/8” NPT x #8 JIC 90° elbow into the fuel in port vacated by the “FOR-SEAL” fitting. Use diesel fuel compatible thread sealer on all NPT threads.



7A-5: Measure and cut the length of the fuel line required, when properly routed and secured, to make the connection from the transfer pump to the fuel inlet fitting at the back of the engine head. Assemble the fuel line with field attachable fuel line end fittings on each end.

Installing the Series 60 Fuel Line Upgrade, cont'd

7A-6. Connect and secure one end of the fuel line assembled in step 4A-5 to the transfer pump fuel “OUT” port.



7A-7. Route and connect the new fuel line to the new 90° #8 JIC fitting just installed in the back of the engine head.

7A-8. Properly tighten all fuel line connections and fittings. Secure the fuel lines with included zip ties to prevent chafing.

Section 4B: Series 60 Engines **WITH** a Secondary Fuel Filter

7B-1. Disconnect and remove the steel fuel line from the “FOR-SEAL” fuel fitting at the fuel “OUT” port on the transfer pump and from the secondary fuel filter, fuel in port.



7B-2. Replace the “FOR-SEAL” fitting in the transfer pump with the “Ported” 16mm ORB x #8 JIC fitting **OR** the “Ported” 1/4” M NPT x #8 M JIC fitting.



OR



1/4” NPT



7B-3. Replace the “FOR-SEAL” fitting in the secondary filter with the “Ported” 14mm x #8 JIC fitting **OR** the “Ported” 1/4” M NPT x #8 M JIC fitting.

Section 7

Fuel Line Upgrade

Section 4B: Installing the Series 60 Fuel Line Upgrade, cont'd

7B-4. Measure and cut the length of the fuel line required to connect the transfer pump fuel “OUT” port to the secondary filter fuel “IN” port.




7B-5. Assemble the fuel line with one straight and one 90°, field attachable fuel line end fitting, as illustrated in.



7B-6. Attach the straight end to the transfer pump “OUT” port and the 90° end to the secondary fuel filter.



7B-7. Disconnect and remove the steel fuel line and shut-off valve from the secondary fuel filter outlet.



7B-8. Install the “Ported” 14mm x #8 JIC fitting **OR** the “Ported” 1/4” M NPT x #8 M JIC fitting in the “Out to Engine” port.

7B-9. Disconnect the OE fuel supply line from the “FOR-SEAL” fuel inlet fitting at the back of the head. Remove the steel line and fitting.



Extended 90° 3/8” NPT x #8 JIC Flare Fitting



7B-10. Install the 90° extended 3/8” NPT x #8 JIC fitting into the fuel in port vacated by the “FOR-SEAL” fitting. Use diesel fuel compatible thread sealer on all NPT threads.

Section 4B: Installing the Series 60 Fuel Line Upgrade, cont'd


7B-11. Measure and cut the length of fuel line required to connect the secondary filter “OUT” port to the 90° #8 JIC fitting just installed in the back of the engine head.



7B-12. Assemble the fuel line with a straight field attachable fuel line end fittings on each end.



7B-13. Connect the end of the new fuel line to the fuel “OUT” port on the secondary fuel filter. Route and connect the other end to the 90° #8 JIC fuel fitting in the head.



7B-14. Properly tighten all fuel line connections and fittings. Secure the fuel lines with included zip ties to prevent chafing.

WIRE HARNESS

***VERY IMPORTANT: The AirDog® wire harness requires a 15 amp fuse.**

The AirDog® wire harness has a low pressure sensor and an amber LED indicator light as standard equipment. The indicator light will illuminate at start-up, remain on for a few seconds, then go off and should remain off unless pressure flow to the engine drops below minimum requirements.

THE AIRDOG® WIRE HARNESS



Securing the AirDog® Wire Harness Relay to the Vehicle

8-1. Secure the AirDog® wire harness relay to the vehicle. This picture shows the relay mounted on the firewall.



8-2. Route the AirDog® wire harness pump motor lead and the fuel pressure sensor lead to the AirDog® unit. Connect the wire harness pump motor lead (labeled “Attach to Motor”) to the AirDog® unit pump motor lead.



8-3. Connect the AirDog® wire harness fuel pressure sensor lead to the AirDog® unit fuel pressure sensor.


Relay Trigger Lead and Indicator Light Lead

The AirDog® Wire Harness Indicator Light lead must be routed through the firewall and to the dash board. The Relay Trigger Lead must be connected to a contact point that is electrically “HOT” when the key is in the “RUN” position. This could be either in a spare fuse holder in the fuse panel or on the ignition switch itself.

Note: DO NOT connect the AirDog® wire harness relay trigger lead to a point that is “HOT” when the key is in the ACCESSORY position.

Routing the Indicator Light and Relay Trigger Lead through the firewall:

8-4. Most Peterbilts and Kenworths have access holes located below the steering column. Remove the plug and route the leads through the hole. For other make trucks, drill a 5/8” hole in firewall to allow entry of the indicator light lead into the cab. Use the grommet to seal around the loom cover.



8-5. Route the AirDog® wire harness trigger lead (red wire with no connector/plug) and indicator light lead through the firewall.

By the Steering Column



Under the Dash



NOTE: Be sure to seal the opening or install a grommet around the wire loom to prevent water leakage and protection from chafing.

Installing the Indicator Light, Cont'd

8-6. Drill a 7/16" hole in the dash at the selected location. Be very careful when drilling. Do not damage components located behind the dash. Remove the nut from the indicator light.



8-7. Install the dash plate and indicator light in the dash. *Note-to adhere plate to dash, you may peel off the paper backing from the backside of the plate to expose adhesive. Reinstall nut and tighten until snug. Connect the positive (orange wire) lead on the wire harness to the positive (marked orange) quick connect terminal on the indicator light (see image above). Then connect the negative (blue wire) lead on the wire harness to the negative (unmarked) quick connect terminal on the indicator light.

8-8. Re-install the removed dash components to their original position.

CONNECTING THE POWER SUPPLY LEADS

The power supply leads can be easily connected to the appropriate contacts on the alternator. Any high amperage terminal that is always "HOT" is OK for the Positive + (RED) lead. Be sure the NEGATIVE - (GREEN) lead is connected to a reliable chassis ground.

8-9. Route the red & green power leads to the alternator. Connect the green (-) ground lead to the alternator **Ground** connection.



8-10. Connect the red (+) positive lead to the alternator **Hot Lead** going to the battery.

NOTE: Secure wire harness with zip ties included in installation kit.

SECTION 9: INITIAL START UP PROCEDURE

The AirDog® is a self priming system. However, to prevent damage to a dry seal and reduce the life expectancy of the system, it is suggested to pre-fill the water separator/pre-filter with diesel fuel to the bottom of the “NUT PLATE”.

- ☐ 9-1. Rub CLEAN diesel fuel or oil on filter seals before installing to ensure a proper seal.
- ☐ 9-2. Pre-fill the water separator/pre-filter with diesel fuel up to the bottom of the nut plate.
- ☐ 9-3. Turn the starter key to the on/run position.
- ☐ 9-4. The AirDog® should now be running and pumping fuel, bleed the fuel line to the engine by loosening the fuel line connection at the engine fitting. As soon as the line is purged of air and pure fuel is observed, properly tighten the fuel fitting.

NOTE: Put a rag or shop towel over and around the fitting to prevent fuel splatter or spray. Catch all spilled fuel and dispose of properly. Wear safety glasses.

- ☐ 9-5. Start the engine.

RECHECK ALL FUEL FITTINGS FOR LEAKAGE AND PROPER TORQUE. BE SURE ALL FUEL LINES ARE PROPERLY ROUTED TO PROTECT FROM EXCESSIVE HEAT AND SECURED TO PROTECT FROM CHAFING AND ABRASION. RECHECK ALL ELECTRICAL LINES AND SECURE AS NECESSARY.

Servicing the AirDog® Fuel Filter and Water Separator/Pre-Filter

The AirDog® low pressure sensor monitors the fuel filter and water separator.

FUEL FILTER: When the fuel filter becomes plugged, the AirDog® Indicator Light will illuminate, indicating it is time for a fuel filter replacement. The AirDog® fuel filters have a typical lifespan of 25,000+ miles, and up to 40,000 miles, as they are made with a high-quality and high-capacity Micro-glass media, as opposed to a paper element, and filter life is affected by many variables. In any case, we do not recommend exceeding 40,000 miles of service with a fuel filter. It is recommended that you keep a replacement AirDog® fuel filter on-hand, ready for replacement when the AirDog® Indicator Light illuminates. When replacing the fuel filter, be sure to clean the under side of the AirDog® base. Rub clean diesel fuel or oil on filter seals before installing to ensure a proper seal. It is not necessary to pre-fill the fuel filter with fuel, the AirDog® will fill the filter and prime the system automatically. Follow the instructions on the filter for proper tightening procedures.



The Water Separator/Pre-Filter

WATER SEPARATOR: Should the water separator/pre-filter or the wire screen in the nipple become plugged, preventing sufficient operating pressure flow to the engine, the Indicator Light will immediately illuminate.

Check the water separator/pre-filter for plugging. Clean or replace as necessary. If the light continues to be on, check the screen in the water separator/pre-filter nipple for debris and plugging. Clean as necessary.

Replace the water separator if it becomes damaged or permanently plugged. Servicing of the water separator simply requires draining at regular intervals. It is suggested to check/drain the water separator weekly or as needed should you experience excessive 'water in fuel' conditions. Before re-installing the water separator after cleaning, be sure to clean the under side of the AirDog® base. Rub clean diesel fuel or oil on filter seals before installing to ensure a proper seal. Follow the instructions printed on the water separator/pre-filter for proper tightening procedures.

When tightening filters with a filter wrench, DO NOT overtighten as doing so may damage the filter.

Caution: Be careful to prevent any contaminants from entering the water separator when removing for cleaning or replacement. Although the water separator pre-filter nipple has a protective wire screen, any debris passing through the system could cause the gerotor to lock up, which can then cause the in-line fuse to blow. Such a pump lock-up is not covered under warranty.

Dispose of waste fuel and used filters properly to protect our environment.

This image shows a full page of blank, lined paper. It features approximately 20 evenly spaced horizontal black lines across the entire width of the page, typical of notebook or legal stationery. The background is a solid off-white color. There are no margins, text, or other markings present.

This image shows a full page of blank, lined paper. It features approximately 20 evenly spaced horizontal black lines across the entire width of the page, typical of notebook or primary writing paper. There are no margins, text, or other markings present.



www.airdogdiesel.com
1-877-463-4373 or
1-573-635-0555

Copyright© 2017
CD Patents, LLC

All Rights Reserved

Bulletin No. 206-1-0405
Revised Oct 14, 2022